

SCHEMA TECNICA / Technical sheet

COMPOSIZIONE / COMPOSITION	90 % POLIESTERE/POLYESTER ; 10% VISCOSA/VISCOSE CON TRATTAMENTO FR/ WITH FR BACKING
ALTEZZA / Width	144 cm/ 56 inches/ $\pm 3\%$
PESO / Weight	1080 gr / mtl / $\pm 5\%$

COD. NOMENCLATURA / TARIFF CODE 58013600

SOLIDITA' DEL COLORE / COLOUR FASTNESS

SOLIDITA' ALLO SFREGAMENTO A SECCO DRY RUBBING	ISO 105-X12 AATCC8	$\geq 4/5$ ordito/warp-trama/weft $\geq 4/5$
SOLIDITA' ALLO SFREGAMENTO A UMIDO WET RUBBING FASTNESS	ISO 105-X12 AATCC8	$\geq 3/4$ ordito/warp-trama/weft $\geq 3/4$ (scale 1-5)
SOLIDITA' ALLA LUCE LIGHT FASTNESS	ISO 105-B02 AATCC 16.3/(40 afu)	$\geq 4/5$ (scale 1-8) ≥ 3 (scale 1-5)

TEST FISICI / PHYSICAL TEST

PILLING	ISO 12945	≥ 4 (scale 1-5)
RESISTENZA DELLE CUCITURE Seam slippage	ISO 13936-2 ASTM D434	<3 mm ordito/warp-trama/weft ≥ 80 lbs
RESISTENZA DEL TESSUTO ALL'ABRASIONE Martindale	ISO 12947-2 ASTM D4157	>50.000giri/rubs martindale >50.000giri/rubs martindale

RESISTENZA AL FUOCO / FLAME RETARDANT

CIGARETTE E MATCH TEST	BS 5852	PASSA/PASS
CALIFORNIA BULLETIN	TB 117	PASSA/PASS
EN 1021 PART/1 cigarette-2 (match)		PASSA/PASS
CLASSE 1 IM	UNI 9175	PASSA/PASS
IMO 2010 FTP PART 8		PASSA/PASS
NFPA 260		PASSA/PASS

LAVAGGIO / CLEANING INSTRUCTION


I DATI SI RIFERISCONO AI CAMPIONI DA NOI TESTATI / THE RESULTS REFER TO THE TESTED SAMPLES